YOUR ROOF IS UNDER ATACK!

PROTECT YOUR INVESTMENT.

THE ONLY PERMANENT SOLUTION...



ELIMINATE MOSS



ELIMINATE ALGAE



ELIMINATE MOLD

CONTACT US AT (866) 526-2228
COPPERCAT.COM



COPPER -vs- ZINC

Zinc COPPE

DOFING STRIPS ROOFING

INSTALLED INSTALLED

COPPER CAT

Bare Roof

+ Cleans the whole slope of your roof*

+ Permanent/ lifelong solution that is durable and will not warp

+ Prolongs water contact maximizing results of released ions

+ Aesthetically pleasing appearance

+ Reusable

- Cleans
partially down the
Slope of your roof

+ Clean algae from shingled roof

- + Release lons
- + Simple to Install
 - + Works on Existing Roofs

+ Time Release - Temporary and vulnerable to damage

and warping

- Water passes right over, no prolonged contact



NOTES ON CHEMICALS

- Chemicals are a temporary solution requiring reoccurring applications.
- Waste of money in the long run.

COPPER CAT

NOTES:

- Eliminates exposure to harmful chemicals.
- Utilizes natural organic chemistry to fight natural organic issues.
- Renews roof system, extends roof life cycle.

* Test results have shown Copper Cat to clean 30ft down roof face.



- The double-sided copper strip is 20x stronger than zinc strips
- The copper oxidizes and eventually blends with 90% of shingle colors for a neat and clean look
- Uses the natural process of water interacting with copper to release ions that prevent growth of algae, mold, moss, etc. on shingles
- Works on new or existing roofs made of asphalt, cedar, slate, etc.
- Helps improve the overall look of a roof by removing black streaks, patchy spots, and other unsightly discolorations

They will continue to work for hundreds of years and can be reused on each new roof.

INSTALLATION INSTRUCTIONS
For further instructions and videos, visit coppercat.com
10°4 - 0

Second Course Should butt up to raised portion of COPPER CAT

From left, use a roofing flat bar to lift bottom of 2nd course. Slide a COPPER CAT strip under 3/4" to where bottom of shingle butts up to COPPER CAT'S raised portion, nail down, repeat to end.

- * Install Copper Cat along all ridge lines for complete coverage.
- * Cover all nail heads with a dab of roofing compound or caulking that is suitable for high temperatures.

Overlap Naii 3/16" Holes Overlap Overlap 3/16"

Hip roof. Refer as cap
Gable roof. *Refer as cap (tear off / new construction)
Gable roof. *Refer as second course (existing shingles / old construction)
Nail COPPER CAT Raised Portion
Lower Shingle Course
Side Profile

FOR MORE INFORMATION AND PRICING CONTACT: